

SHUTTEROL RA

TECHNICAL DATA SHEET

SOLVENT BASED, READY-TO-USE, FORM-RELEASE AGENT

Description

SHUTTEROL RA is specially formulated blend of mineral oils and chemicals having release properties which are superior to those of a conventional mould oil. The chemicals react with the alkali in the concrete to form a thin water repellent skin on the surface of the mould, thereby enabling easy striping from concrete and acting as a protection to steel and wooden formwork.

SHUTTEROL RA is supplied as a pale straw-coloured liquid ready for direct application and use.

Uses

To provide quick, clean and easy stripping of moulds, and formwork and ensure high quality fair-faced and stain-free concrete.

Advantages

- Environmental friendly Non-hazardous, having flash point >160°C
- Water-resistant chemical barrier Ensures fast, clean stripping of forms
- No residue transfer Stain-free & less voids
- Does not harm concrete compatible
- Can be used on all types of formworks
- Minimizes cleaning of shutters before re-use
- Reduces opportunity of damage to formwork, extending usable life.
- Suitable for use with steam cured concrete.
- Ready to use

Characteristics

• Form : Liquid

• Composition : Blend of release agents in

hydrocarbon carrier

• Relative density : 0.87 ± 0.03 at 25° C

• Chloride content : Nil (as per BS 5075 part I)

Freezing point : -10°C
Flashpoint : >160°C

Directions of for use

Apply before the first casting and thereafter reapply immediately after stripping and cleaning the mould.

Lightweight horticultural sprayers (knapsack type) are ideal as SHUTTEROL RA is finely atomized to give a uniform coating.

Excessive application should be avoided.

Alternatively, application may be made by a fine haired brush, only a very thin coating should be made and any excess removed.

If after the first application, the SHUTTEROL RA is completely absorbed into new timber or plywood, a further application should be made before filling the moulds or formwork.

Coat forms liberally before storing to keep rust free. To return forms to service, sweep down and recoat with SHUTTEROL RA.

Packaging

SHUTTEROL RA is supplied in 200 litre drums, 20 litre and 5 litre containers.

Coverage

A coverage between 20 to 60m2 per litre is possible depending upon the porosity and texture of mould surface.

Storage and Shelf life

SHUTTEROL RA must be stored where temperatures do not drop below +5°C. Store under cover, out of direct sunlight and protect from extremes of temperature.

Shelf life is 12 months when stored as above.

Safety precautions

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs (which can also be tainted with vapour until product fully cured or dried). Treat splashes to eyes and skin immediately. If accidentally ingested, seek immediate medical attention. Keep away from children and animals. Reseal containers after use. Do not reuse containers for storage of consumable item. For further information refer to the material safety data sheet. MSDS available on demand or on FIRSTCHOICE SPECIALITY CHEMICALS web site.



TECHNICAL DATA SHEET

SOLVENT BASED, READY-TO-USE, FORM-RELEASE AGENT

Note

All Technical Data Sheets of FIRSTCHOICE SPECIALITY CHEMICALS are updated on regular basis; it is the user's responsibility, to obtain the most recent issue. Field services where provided, does not constitute supervisory responsibility, for additional information contact our local representative.

Disclaimer

Whilst any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control.

FIRST CHOICE SPECIALITY CHEMICALS PRIVATE LIMITED

Factory Address:

Ahmedabad-Moraiya, Changodar,Bavla Highway,PS: Changodar,District-Ahmedabad,Gujarat, PIN- 382213.

Shyam Business Park, Durgapur Express way, Dist - Singur, West Bengal, Pin - 712306

www.fcsc.co.in

Helpline no: 3335000230

Office Address : "SHRACHI TOWERS"

3rd Floor, 686, Anandpur, E. M. Bypass,

Kolkata - 700 107. www.fcsc.co.in

Helpline no: 3335000230